

Model: PL-808 Family

G.hn over Power Line or Coax | 802.11ac Wave-2 AC1200 | DFS

- G.hn Wave2
- 5GHz 2x2, 2.4GHz 2x2
- 1x 10/100/1000BASE-T Ethernet RJ45 ports
- Mobile App Management
- TR069, TR098, TR181



PL-808C (Coax)



PL-808 (PowerLine)



WPL-808C (Coax+WiFi)



WPL-808 (PowerLine + WiFi)

PL-808/C FEATURES

- G.hn Wave2 over Coax (PL-808C) / Powerline (PL-808)
- 1 Gigabit Ethernet LAN
- Push-button Pairing and Status LEDs
- Support TR-069 for ACS remote configuration / Management
- Integrated with mobile management application

WPL-808/C FEATURES

- G.hn Wave2 over Coax (WPL-808C) / Powerline (WPL-808)
- 1 Gigabit Ethernet LAN
- Support TR-069 for ACS remote configuration / Management
- Push-button Pairing and Status LEDs
- Integrated with mobile management application

GENERAL

■ Weight	PL-808/C 200g WPL-808/C 400g
■ Operating Temperature	Operating: -5°C ~ +45°C Storage: -20°C to +85°C
■ Operating Humidity	5% to 95% non-condensing humidity & 86kPa ~ 106kPa altitude
■ Dimensions HxWxD	PL-808/C 120mm x 65mm x 22mm WPL-808/C 120mm x 65mm x 42mm

MOBILE MANAGEMENT APPLICATION

- Configuration tool to monitor and manage devices
- Troubleshooting and diagnosing tool to perform speed test, Wi-Fi neighbor scan, and analysis
- Android and iOS support